

Elektrolift Magnets:

- Deep magnetic field to reach irregular objects
- High surface strength for flat steel objects
- ♦ Continuously-welded solid construction
- Multiple Elektrolifts can be used in tandem
- ♦ Maintenance-free
- No bolts, screws or nuts that could loosen, makes the Elektrolift trouble-free service.
- ♦ Rated for continuous duty



Dings Elektrolift Magnets are all-welded, steel constructed magnets built to take punishing actions encountered when hoisting steel in factories. Elektrolifts are the preferred answer when searching for a better way to hoist parts on tool beds, grinders, etc. and to load trucks, bins and furnaces. They ship ready to be installed.

Diameters of 4", 8", 13", and 18" are available.

Ready for shipment. Our magnetic experts can custom design an Elektrolift Magnet to suit your application needs

More Dings Company Magnetic Separation Equipment

Eddy Current Separator

Separate non-ferrous metal



Deep Draw Drum Magnet

Lifetime warranty on magnetism



Overhead Stationary Electromagnet

20-year warranty on coil burnout



Ferroplate Magnet

Lifetime warranty on magnetism



Pneumatic Inline Magnet

Powerful rare earth magnets available



Quick Clean Perma Chute Magnet

Lifetime warranty on magnetism



Rare Earth Ferroplate Magnet

More holding power



Overhead Self-Cleaning Electromagnet

20 year warranty on coil burnout



Overhead Self-Cleaning Permanent Magnet

Lifetime warranty on magnetism



Severe Duty Overhead Self-Cleaning Electromagnet

"Durabelt" Stainless steel pads and cleats



MRF (Material Recovery Facility) Overhead Self-Cleaning Electromagnet

3" high cleats



Magnetic Head Pulley

Available in 3 different strength series



Engineering Driven - Customer Service Focused



Dings Company Magnetic Group engineering and sales staff work together from our Milwaukee, WI factory to provide outstanding customer service from experts in magnetic separation. We listen to our customers to gain an understanding of their needs and apply our experience in their trade to provide magnetic separation equipment that is sized and positioned for the best possible performance in their specific application.



Elektrolift Magnet Quote Request

Company:	Quote Required Date:
Address:	Contact Person:
City, State, ZIP:	Contact Email:
Phone/Cell:	Email Completed RFQ to: magsales@dingsco.com
Date Equipment Required by:	
Information for Lifting Applications	
Maximum Plate Thickness: inches	
Maximum Plate Length: inches	Thickness
Maximum Plate Width: inches	Width
Maximum Plate Weight: lbs	Width
Description of Largest and Smallest Material to be Lifted:	
Supply Requirements: Volts:	Phase: Cycles Per Second (Hz):
Special Requirements:	