



# Dings magnetic group

## Magnetic Head Pulley Request for Quote

Company: \_\_\_\_\_ Quote Required Date: \_\_\_\_\_

Address: \_\_\_\_\_ Contact Person: \_\_\_\_\_

City, State, ZIP: \_\_\_\_\_ Contact Email: \_\_\_\_\_

Phone/Cell: \_\_\_\_\_ Email Completed RFQ to: magsales@dingsco.com

Date Equipment Required by: \_\_\_\_\_

### Application Information

Application: \_\_\_\_\_

Description of Material Being Conveyed: \_\_\_\_\_

Size of Material Being Conveyed: \_\_\_\_\_

Description of Largest Pieces of Ferrous Requiring Removal: \_\_\_\_\_

Description of Smallest Pieces of Ferrous Requiring Removal: \_\_\_\_\_

Type of Equipment Being Protected: \_\_\_\_\_

Is This a Recycling Applications - Collecting Ferrous Metal:      Yes                  No

Belt Width: \_\_\_\_\_ inches                                  Depth of Material on Belt at Pulley: \_\_\_\_\_ inches

Belt Speed: \_\_\_\_\_ fpm    Current Pulley Diameter: \_\_\_\_\_ inches

Belt Capacity: \_\_\_\_\_ tph    RPM: \_\_\_\_\_

Special Circumstances That May Affect Application: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

### Magnetic Head Pulley Selection

Pulley Series Selection:	Dings Standard:		Dings Heavy-Duty:		Dings DFC Ultra:	
Pulley Diameter:	6 inches	8 inches	12 inches	15 inches	18 inches	
	20 inches	24 inches	30 inches	36 inches	42 inches	

### Magnetic Head Pulley Options

Note: Optional pulley lagging - typically used in outdoor applications - provides extra engagement between the conveyor belt and pulley in wet conditions

Lagging:                                  Yes                  No

Vulcanized Rubber:

Rough Top:

Special Requests:

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_