



# Dings magnetic group

## Eddy Current 9500 Model Request for Quote

Company: \_\_\_\_\_ Quote Required Date: \_\_\_\_\_

Address: \_\_\_\_\_ Contact Person: \_\_\_\_\_

City, State, ZIP: \_\_\_\_\_ Contact Email: \_\_\_\_\_

Phone/Cell: \_\_\_\_\_ Email Completed RFQ to: magsales@dingsco.com

Date Equipment Required by: \_\_\_\_\_

### Application Information

Application: \_\_\_\_\_

Type & Size of Non-Metallics to be Separated: \_\_\_\_\_

Type of Ferrous Removal Prior to Eddy Current: \_\_\_\_\_

Type & Size of Non-Ferrous Metals to be Separated: \_\_\_\_\_

Method of Feeding Eddy Current: \_\_\_\_\_

Feed Rate: \_\_\_\_\_ fpm      Feed Width: \_\_\_\_\_ inches      Moisture Content: \_\_\_\_\_ % Percent

Burden Depth: \_\_\_\_\_ inches      Tons Per Hour: \_\_\_\_\_ T/hr

Location of Eddy Current:      Indoor      Outdoor      Bulk Density: \_\_\_\_\_ lbs/ft<sup>3</sup>

Ambient Temperature: \_\_\_\_\_ °F min      \_\_\_\_\_ °F max

Supply Requirements:      Volts: \_\_\_\_\_      Phase: \_\_\_\_\_      Cycles Per Second (Hz): \_\_\_\_\_

Hours of operation: \_\_\_\_\_

Special Requirements: \_\_\_\_\_

### Eddy Current Belt Width Selection

Belt Width:	
36 inches	42 inches
48 inches	54 inches
60 inches	72 inches

### Eddy Current Options

Fixed Speed Control Panel:
Belt Tracking Sensors:      Splitter Assembly:
Standard Variable Speed Belt & Rotor Control Panel:
NON-Standard Variable Speed Belt & Rotor Control Panel: