Dings magnetic group

Heavy-Duty Pit Magnet:

- Square or rectangular models
- Available in any width or length from 1 to 5 feet
- Heavy duty all welded construction
- ◊ 304 stainless steel
- Large 2"x 2" square tubes
- Tube walls that enclose magnetic material are heavier gauge than standard grate magnets for extra rigidity
- ◊ 2-1/2" space between tubes
- Optional deflectors direct flow toward the tubes for maximum separation.



*Shown with deflectors

Dings' Heavy-Duty Pit Magnet

Extra sturdy grate magnet mounts securely over receiving pit opening to remove ferrous metal from grain stream. Larger 2" square magnetic tubes and wider tube spacing allow the pit magnet to be used in high volume applications. Sizes range from one to five feet square or rectangular.

The Dings Pit Magnet was designed specifically for grain handling facilities, continuously removing nails, screws, wire, tools, and other tramp iron. It's also ideal for other high volume processing operations with free-flowing powders or granular materials.



On Magnetism for all Permanent Magnets

For quote contact the Dings' factory. Phone: 414-672-7830 Email: magsales@dingsco.com

Call us for Expert Support of Dings Co. Equipment - Regardless of its Age

Superior Grade Ceramic VIII

Dings Co. uses the best grade of ceramics for magnet tubes, ensuring a stronger, longer lasting magnetic field. Ceramic VIII has a better resistance to demagnetization than Ceramic V or other lower grade materials.

This resistance is particularly important in grates because of the arrangement of polarities inside the tubes. For maximum separating power, the magnetic components must be assembled in the tubes with like poles facing each other. However, these repelling poles create a strong demagnetizing force which can weaken the performance of the grate magnet. Ceramic VIII was developed specifically to overcome this negative effect, making it the ideal material for grate magnets.

More Dings Company Magnetic Separation Equipment

Eddy Current Separator Overhead Stationary Electromagnet Deep Draw Drum Magnet Separate non-ferrous metal 20-year warranty on coil burnout Lifetime warranty on magnetism DINGS Ferroplate Magnet **Pneumatic Inline Magnet** Quick Clean Perma Chute Magnet Lifetime warranty on magnetism Powerful rare earth magnets available Lifetime warranty on magnetism Rare Earth Ferroplate Magnet **Overhead Self-Cleaning Overhead Self-Cleaning Permanent** Electromagnet More holding power Magnet Lifetime warranty on magnetism 20 year warranty on coil burnout Severe Duty Overhead Self-Cleaning MRF (Material Recovery Facility) **Magnetic Head Pulley** Electromagnet **Overhead Self-Cleaning Electromagnet** Available in 3 different strength series "Durabelt" Stainless steel pads and cleats 3" high cleats

Engineering Driven - Customer Service Focused



Dings Company Magnetic Group engineering and sales staff work together from our Milwaukee, WI factory to provide outstanding customer service from experts in magnetic separation. We listen to our customers to gain an understanding of their needs and apply our experience in their trade to provide magnetic separation equipment that is sized and positioned for the best possible performance in their specific application.