Overhead Magnet Quote Request for Recycling

Company:	Quote Required Date: Contact Person: Contact Email: Email Completed RFQ to: magsales@dingsco.com *You Must Select One to Print: Imperial Metric
Information for Aggregate Applications Type of Material Being Conveyed: Belt Width: Belt Speed: Max Lump Size: Requested Magnet Suspension Height: Conveyor Inclined? Yes No Inclined: Supply Requirements: Volts: Description of Largest & Smallest Size of Metal to be Removed	Belt Capacity: Max. Burden Depth: o degrees Phase: Cycles Per Second (Hz):
a) Description of Largest & Smallest Size of Metal to be Removed suspension of magnet suspension height. Over Conveyor Mounted Suspension Height Magnet Belt Travel Direction	b) Description of burden depth for flat belts (no idler angle/trough depth entries needed) Burden Depth
Overhead Magnet Selection Electromagnet Permanent Overhead Mounting Selection: Inline Cross-Belt Over Head Pulley Cross-Belt Over Conveyor	Non-Magnetic Material Magnetic Material

Overhead Magnet Options

Armor-Clad Durabelt

Special Requirements:

Dust Cover Hazardous Location
Pulley Guard CSA Approved Model
High Temp. Belt Zero Speed Switch

ver. 1/25

*Note: Electromagnets Require a Rectifier for Operation: Rectifier: Yes: No:

ETL Listed Model

Rectifier Options

Hazardous Location